



SIDER-ROOF

SEAMLESS ELASTOMERIC WATERPROOFING ROOF COATING

1.0 DESCRIPTION

1.1 General

Sider-Roof is a unique system that combines strength, flexibility, and reflectivity to protect inaccessible roofs, concrete roofing, or cement-based roofing systems against severe weather and pollutants.

2.0 INSTALLATION

2.1 Surface preparation

Surfaces must be power washed to remove dirt, paint, rust, excessive chalk, mildew, and other foreign matter which could prevent proper adhesion. Prime surfaces using Sider-Roof Primer. Surfaces must be completely dry prior to coating with **Sider-Roof**.

2.2 Mixing Instructions

Sider-Roof has excellent suspension and requires minimal stirring. **DO NOT THIN.**

2.3 Application

Sider-Roof is a two-coat application process. Simply apply **Sider-Roof** with a soft brush (avoid excessive brushing), roller, or airless sprayer. Apply the light gray base coat and allow 24 hours after the initial application before applying the white finish coat.

2.4 Limitations

Apply **Sider-Roof** when surface and ambient temperatures are above 50° F and below 95° F during application and drying period. Do not apply when rain is in the forecast. Application during low temperature or high humidity will extend drying time. Allow 4-6 hours for coating to dry prior to being subjected to rain, heavy dew, or temperatures below 50° F. **KEEP FROM FREEZING.**

2.5 Maintenance

It is recommended that installation be checked on a regular maintenance schedule. Small area touch up can be made, if needed, following the recommended application procedures.

3.0 MISCELLANEOUS

3.1 Packaging

5 gallon pails

3.2 Coverage

250 sq. ft. per 5 gallons per coat

3.3 Colors

Sider-Roof is available in gray, black, terracotta, white, and yellow.

3.4 Technical Application Assistance

For technical inquiries, contact Sider-Oxydro, Inc. at **Toll Free: 888-743-3750**.

3.5 Professional Qualifications

Installation shall be performed by contractors with a minimum of 5 years documented experience in roof coatings application or approved by Sider-Oxydro, Inc. All applicators should be able to provide several references from general contractors, architects or other applicable references for review by Sider-Oxydro, Inc.

3.6 Storage and Shelf Life

Store in a dry environment, away from direct sunlight, rain, and freezing temperatures.

Shelf life is 6 months in the original sealed packaging, properly sheltered in a dry environment.

3.7 Commercial Names

SIDER-ROOF

*And now, enjoy using **SIDER-ROOF** and benefit from this revolutionary technology developed by Sider-Oxydro, Inc., innovative leaders in the construction industry since 1937.*

While every effort has been made to be comprehensive and accurate, the publisher cannot accept any liability for omissions or errors. Users should contact Sider-Oxydro for the product(s) referred to in this specification to ensure that any information used to make decisions about the product is as up-to-date and complete as possible.